

Self contained clutches

Overrun. speed inner race	Overrun. speed outer race	Overrun. Clutch	Indexing Clutch	Back-stop	Bores Ø [mm]	Torques [Nm]	Types
Low	~			x	25-90	375-4,875	RSBW
Low	~		x	x	20-120	265-11,000	AV
Medium	High	x	x	x	12-250	55-287,500	AL-ALP
Medium	High	x	x	x	12-250	55-287,500	AL..F2D2
Medium	High	x	x	x	12-250	55-287,500	AL..F4D2
Medium	High	x	x	x	12-250	55-287,500	ALP..F7D7
Medium	High	x	x	x	12-250	55-250,000	AL..KEED2
Medium	High	x	x	x	12-120	50-20,000	AL..KMSD2
Medium	High	x	x	x	12-150	55-70,000	GFR-GFRN
Medium	High	x	x	x	12-150	55-70,000	GFR..F1F2/ F2F7
Medium	High	x	x	x	12-150	55-70,000	GFRN..F5F6
Medium	~			x	12-150	55-70,000	GFR..F2F3
Medium	~			x	12-150	55-70,000	GFR..F3F4
High	Medium	x	x	x	dec-80	379-6,900	FS0300-700
High	Medium	x	x	x	57-175	9,660-36,612	FS0750-1027
~	High	x			12-150	288-45,000	AL..G